

Exterior Lines of T. 6 S., R. 31 E., W.M.

Chains		Feet
	N. on E. Bdy. of Sec. 12 Var. 17° 30' E.	
2.50	Brook, 5 lks. wide, runs. S.W.	
2.75	Ascend hill, brs. N.E. and S.W.	
8.28	Top of hill, brs. N.E. and S.W.	
40.00	Set a basalt stone, 14 x 10 x 8, in a mound of stone, for $\frac{3}{4}$ Sec. Cor.	
80.00	Set a basalt stone, 16 x 10 x 7, and dug pits for Cor. to Secs. 1, 6, 7, 12.	
	Land; N. 71.72 Chs. rolling; remainder hilly Soil; 2nd rate. Scattering pine on S., 5 Chs.	
	N. on E. Bdy. Sec. 1 Var. 20° 15' E.	
25.40	Ravine, course W.	
40.00	Set a basalt stone, 16 x 10 x 4, in a mound of stone, for $\frac{1}{4}$ Sec. Cor.	
71.84	Intersect 1st Standard Parallel, 441 lks. E. of standard Cor. to Secs. 35 and 36, Rgs 31 E. Set a basalt stone, 24 x 12 x 6, and dug pits for closing Cor., from which A Pine, 4 ins. in diam. brs. N. 42° E., 190 lks. dist. Land; rolling Soil; 2nd rate. Some scattering pine and heavy bunch grass. June 22, 1881.	
	Subdivisional Lines of T. 6 S., R. 31 E., W.M. As surveyed By Rufus S. Moore and Under Joint Contract No. 382. Dated March 23, 1881.	
	N. bet. Secs. 35 and 36	
3.60	To John Days river, N. fork, 150 lks. wide, runs W. Set a flag at this point, thence cross over to pt. where flag brs. due S., thence run a base W. 150 lks. the	