

Exterior Lines, T 7 S R 32 E W M.

Chains

40.00 Set an alder post for $\frac{1}{2}$ Sec. Cor.
 A fir, 20 ins. diam., brs. N.38°W., 26 lks. dist.
 A fir, 10 ins. diam., brs. S.73°W., 39 lks. dist.

40.35 John Day River, 150 lks. wide, runs N.W.
 Offset N., then run E. on offset 3 chs., then S. to true
 line.
 Foot of hill brs. N.W. & S.E.
 Ascend hill from river N.W. & S.E.

80.00 To Tp. Cor. to Tps. 6 & 7 S., Rs. 32 & 33 E.
 Land; hilly & mountainous.
 Soil; 2nd rate.
 Heavy fir, pine & tamarack timber.
 Dense young fir, pine, arrowwood & mountain laurel.

June 8th, 1881.

Exterior Lines, T 6 S R 32 E W M. (East Bdy.)
 As surveyed by Frank W. Campbell,
 Under Contract No. 468,
 Dated April 12, 1883.

I begin at the established Cor. to Tps. 6 & 7 S., Rs. 32
 and 33 E., which is a post, 5 ins. sq., marked
 T 6 S S 36 on N.W.
 R 32 E S 1 on S.W.
 S 31 on N.E. and
 R 33 E S 6 on S.E. faces,
 with 6 notches on each edge, from which
 A tamarack, 18 ins. diam., brs. N.8°W., 34 lks. dist.,
 marked T 6 S R 32 E S 36 B T.
 A pine, 20 ins. diam., brs. N.76°E., 31 lks. dist.,
 marked T 6 S R 33 E S 31 B T.
 A pine, 24 ins. diam., brs. S.27°E., ~~S 6 B T.~~ ^{40 lks. dist.}
 marked T 7 S R 33 E S 6 B T.
 A pine, 26 ins. diam., brs. S.37°W., 27 lks. dist.,
 marked T 7 S R 33 E S 1 B T.

Thence I run
 N. bet. Secs. 31 & 36.