

Exterior Lines, T 6 S R 33 E, W M.

Chains

A mahogany, 6 ins. diam., brs. S. 88° W., 51 lks. dist.,
marked $\frac{1}{2}$ S B T.

A pine, 10 ins. diam., brs. S. 62° E., 85 lks. dist.,
marked $\frac{1}{2}$ S B T.

76.80 Intersect the 1st Standard Parallel S., 7 lks. E. of S. Cor.
to Secs. 35 & 36, T 5 S R 33 E., at which point, I
Set basalt stone, 20 x 13 x 6 ins., 15 ins. in ground, for
Closing Cor. to Secs. 1 & 6, T 6 S., Rs. 33 & 34 E., marked
with C.C. and 6 notches on S., E. & W. edges, from which
A pine, 4 ins. diam., brs. S. 44° W., 11 lks. dist.,
marked C C T 6 S R 33 E S 1 B T.
A pine, 4 ins. diam., brs. S. 40° E., 59 lks. dist.,
marked C C T 6 S R 34 E S 6 B T.
A pine, 3 ins. diam., brs. N. 20° W., 100 lks. dist.,
marked T 5 S R 33 E S 35 B T.

Land; mountainous.

Soil; 2nd rate.

Densely covered with forests of pine, fir, spruce & tamar-
rack, 76.80 chs.

June 23, 1883.

Subdivisional Lines, T. 6 S., R. 33 E., W. M.
As surveyed by same U.S. Deputy Surveyor,
Under same Contract and date.

I commenced at the Cor. to Secs. 1, 2, 35 & 36, on the
S. Bdy. of the Tp., which is a post, 4 ins. sq., firmly
set in ground and marked,

T 6 S S 36 on N.E.

R 33 E S 1 on S.E.

T 7 S S 2 on S.W.

S 35 on N.W. faces, with

1 notch on E. and

5 notches on W. edges, from which

A fir, 10 ins. diam., brs. N. 60° E., 26 lks. dist.,
marked T 6 S R 33 E S 36 B T.

A fir, 10 ins. diam., brs. S. 42° E., 17 lks. dist.,