Subdivisional Lines, T 6 S R 34 E W M.

Chains.	
	T 6 S S 33 on N.E.
	R 34 E S 4 on S.E.
	T 7 S S 5 on S.W. and
	S 32 on N.W. faces, with
	4 notches on E. and
	2 notches on W. edges;
	from which
	A tamarack, 12 ins. diam.,brs. N.36°E., 8 lks. dist., marked T 6 S R 34 E S 33 B T.
	A tamarack, 18 ins. diam.,brs. S.6°E., 18 lks. dist., marked T 7 S R 34 E S 4 B T.
	A tamarack, 10 ins. diam.,brs. S.54°W., 12 lks. dist., marked T 7 S R 34 E S 5 B T.
	A fir, 8 ins. diam.,brs. N.18°W., 12 lks. dist., marked T 6 S R 34 E S 32 B T.
	I run
	N. bet. Secs. 32 & 33.
	Var.19°E.
	Descend along gentle slope, facing N.E.
40.00	Set tamarack post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for ¼ Sec. Cor., marked ¼ S on W. face; from which,
	A tamarack, 8 ins. diam.,brs. N.48°W., 18 lks. dist., marked ¼ S B T.
	A pine, 9 ins. diam.,brs. S.40°E., 4 lks. dist., marked ¼.S B T.
	Descend over rolling ground.
64.00	Mountain trail, course E. & W.
80.00	Set pine post, 4 ft. long, 4 ins. sq., 24 ins. in ground for Cor. to Secs. 28, 29, 32 & 33, marked
	T 6 S S 28 on N.E.
	R 34 E S 33 on S.E.
	S 32 on S.W. and
	S 29 on N.W. faces, with
	4 notches on E. and